

# Pedidos

## Como adicionar pedido via API ?

POST: [http://www.nomedoseusite.com.br/api\\_ds\\_orders.php?action=add\\_orders](http://www.nomedoseusite.com.br/api_ds_orders.php?action=add_orders)

### Header Parameter

Token  
Secret  
E-mail

### Format

base64\_encode()  
base64\_encode()  
base64\_encode()

Parameter	Format	Description
products_id	JSON	Use the API to list the order data to get the product_id Format: int(11)
products_quantity	JSON	Quantity number Only number is required
products	JSON	products_id & products_quantity
delivery_firstname	JSON	Firstname Format: varchar(255) * FIELD REQUIRED
delivery_lastname	JSON	Lastname Format: varchar(255) * FIELD REQUIRED
delivery_street_address	JSON	Street address Format: varchar(255) * FIELD REQUIRED
delivery_number	JSON	Delivery Number Format: varchar(255) * FIELD REQUIRED
delivery_suburb	JSON	Suburb Format: varchar(255) * FIELD REQUIRED
delivery_city	JSON	City Format: varchar(255) * FIELD REQUIRED
delivery_postcode	JSON	Post Code Format: varchar(11) * FIELD REQUIRED
delivery_country	JSON	Country Name Format: varchar(255) * FIELD REQUIRED
delivery_state	JSON	State Name Format: varchar(2) * FIELD REQUIRED
payment_method	JSON	Use the API to payment_method

# Pedidos

Format: varchar(255)

\* FIELD REQUIRED

Use the API to

calculate\_shipping

Format: varchar(255)

\* FIELD REQUIRED

shipping\_method JSON

## PHP Sample

```
// sample add_orders

$url = $domain_url . '/api_ds_orders.php?action=add_orders';

$data_products[0] = array("products_id" => "215", // Example: 130
(Only number is required) * FIELD REQUIRED
    "products_quantity" => "1" // Example:
1 (Only number is required) * FIELD REQUIRED
    );

$data_products[1] = array("products_id" => "215", // Example: 130
(Only number is required) * FIELD REQUIRED
    "products_quantity" => "1" // Example:
1 (Only number is required) * FIELD REQUIRED
    );

$data = array("products" => $data_products, // * FIELD REQUIRED
    "delivery_firstname" => utf8_encode("Name"), // Example: Name (F
irstname) * FIELD REQUIRED
    "delivery_lastname" => utf8_encode("Surname"), // Example: Surna
me (Lastname) * FIELD REQUIRED
    "delivery_street_address" => utf8_encode("Street address"), // E
xample: Street address (Street Address) * FIELD REQUIRED
    "delivery_number" => "123", // Example: 123 (Delivery Number) *
FIELD REQUIRED
    "delivery_suburb" => utf8_encode("Suburb"), // Example: Suburb (
Suburb) * FIELD REQUIRED
    "delivery_city" => utf8_encode("Sao Paulo"), // Example: Sao Pau
lo (City) * FIELD REQUIRED
    "delivery_postcode" => "04267000", // Example: 04267000 (Post Co
de) * FIELD REQUIRED
    "delivery_country" => utf8_encode("Brazil"), // Example: Brazil
(Country) * FIELD REQUIRED
    "delivery_state" => utf8_encode("SP"), // Example: SP (State) *
FIELD REQUIRED
    "payment_method" => "paypal_standard", // Example: paypal_stand
ard (Payment Method) * FIELD REQUIRED
    "shipping_method" => "sedex" // Example: sedex (Shipping Method)
* FIELD REQUIRED
    );
```

# Pedidos

```
$data_string = json_encode($data);  
// print_r($data_string);  
// die;  
  
$ch = curl_init($url);  
curl_setopt($ch, CURLOPT_CUSTOMREQUEST, "POST");  
  
curl_setopt($ch, CURLOPT_POSTFIELDS, $data_string);  
  
curl_setopt($ch, CURLOPT_RETURNTRANSFER, true);  
curl_setopt($ch, CURLOPT_SSL_VERIFYPEER, false);  
  
curl_setopt($ch, CURLOPT_HTTPHEADER, array(  
    'Content-Type: application/json',  
    'Cache-Control: no-cache',  
    'Token: ' . base64_encode($token),  
    'Secret: ' . base64_encode($secret),  
    'E-mail: ' . base64_encode($email),  
    'Content-Length: ' . strlen($data_string))  
);  
  
$result = curl_exec($ch);  
curl_close($ch);  
  
print_r($result);  
    // sample add_orders eof
```

## Return Error:

code  
message

## Return Success:

code  
products\_model  
products\_id  
message

ID de solução único: #2575

Autor: : MFORMULA FAQ

Última atualização: 2021-03-06 12:30